(19) World Intellectual Property Organization

International Bureau



TO INTERNITORIS IN CONTROL TO THE CONTROL OF THE CO

(43) International Publication Date 24 February 2005 (24.02.2005)

PCT

(10) International Publication Number WO 2005/018121 A1

- (51) International Patent Classification⁷: H04B 1/60, 7/216, H04Q 7/00
- H04J 3/06,
- (21) International Application Number:

PCT/US2003/024348

- (22) International Filing Date: 4 August 2003 (04.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): THOM-SON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne Cedex (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LITWIN, Louis, Robert [US/US]; 34-14 Quail Ridge Drive, Plainsboro, NJ 08536 (US). KOSLOV, Joshua, Lawrence [US/US]; 10 Fairway Drive, Hopewell, NJ 08525 (US).


- (74) Agents: TRIPOLI, Joseph, S. et al.; Thomson Licensing Inc., 2 Independence Way, Suite 200, P. O. Box 5312, Princeton, NJ 08543-5312 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: ADAPTIVE FRAME SYNCHRONIZATION IN A UNIVERSAL MOBILE TELEPHONE SYSTEM RECEIVER



<u>115</u>

0/C007 OM

(57) Abstract: A Universal Mobile Telephone System (UMTS) receiver (115) performs slot synchronization using a received primary synchronization channel (PSCH) (205). Subsequent to completion of slot synchronization, the UMTS receiver (115) adaptively controls the duration of processing of the secondary synchronization channel (SSCH) (210) for determining frame synchronization.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.